



速装型泵头

产品型号：HandyPump

流量范围：0.0033-365.69mL/min



单通道



双通道



单通道



双通道

产品简介

HandyPump系列速装型泵头，外形美观，体积小。前置旋钮开启上压块，节省操作空间。可较快更换软管，具有自适应卡管装置。

单通道、双通道任意选择，适用5种不同尺寸的软管，以满足不同的流量要求。



技术参数

泵头型号	通道数	管号	内径×壁厚 (mm)	毫升 / 转	转速 (rpm)	流量范围 (mL/min)	重量 (kg)
HandyPump01	单通道	13#	0.8×1.6	0.033	0.1~300	0.0033~10.03	0.224
		14#	1.6×1.6	0.187		0.0187~56.09	
		19#	2.4×1.6	0.371		0.0371~111.17	
		16#	3.1×1.6	0.636		0.0636~190.76	
		25#	4.8×1.6	1.219		0.1219~365.69	
HandyPump02	双通道	13#	0.8×1.6	0.033	0.1~300	0.0033~10.03	0.224
		14#	1.6×1.6	0.187		0.0187~56.09	
		19#	2.4×1.6	0.371		0.0371~111.17	
		16#	3.1×1.6	0.636		0.0636~190.76	

安装步骤



1. 逆时针扳动旋钮 180°, 打开压块。



2. 用双手将软管自然放入滚轮与上压块之间, 轻轻拉紧。



3. 顺时针扳动旋钮 180°, 使压块下压到位, 压紧软管。

尺寸图

(单位: mm)

